



Key Features

Fully compliant to BS8000-2: 2018



Standalone system controller for one zone



Light grey double gang plate



LED indication and Braille enhanced accept button



Combined controller and PSU



Overview

Emergency Voice Communication (EVC) systems empower individuals with disabilities or mobility challenges to request assistance during emergencies.

Building owners have the responsibility of ensuring the safety of everyone who uses their property and building regulations mandate the installation of suitable emergency assistance alarm systems in specific areas, including disabled toilets.

Crisis Assist Emergency Assistance Systems offer a comprehensive solution to provide aid and support during emergency situations. Incorporating features and components to facilitate quick response and assistance to individuals in need, Crisis Assist enhances safety and security by providing timely assistance and support during emergencies, helping to minimise risks and mitigate the impact of crisis situations.

Crisis Assist Disabled Toilet Alarm Controller, 1 Line

The Crisis Assist Disabled Toilet Alarm Controller, with one line (zone), provides clear audio and visual feedback, housed in a sleek light grey finish that seamlessly integrates into any environment.

Designed to enable the continual monitoring of a single zone, the Crisis Assist disabled toilet alarm controller should be located in a permanently staffed area where assistance calls can be received and actioned as quickly as possible.

During an alert, the controller features audio and visual indication of an alarm. An integrated buzzer sounds and the unique blue “halo” indicator around the Accept button flashes for visual indication of a call. Once the staff member presses the braille-enhanced Accept button, the sounder is muted and the LED halo turns solid until the alarm is cancelled or reset at the origin of the alarm.

Tech Specs

Standards	BS8000-2: 2018 EMC: EN 55035:2017+A11:2020, EN 55032:2015+A1:2020 LVD: EN IEC62368-1:2020+A11:2020
Supply	230VAC +- 10%
Battery Backup	Optional 600mA NIMH Rechargeable Battery
Cabling	Two core 0.4mm to 2.5mm CSA (max return resistance 10 Ohms)
Relay Output	0V 1A NO Volt Free
Alarm Output	50-80dBA
Dimensions (W x H)	146mm x 86mm
Back Box Information	35mm deep double gang flush or round corned metal surface box

Ordering Information

Part Number	Description
36-400	Crisis Assist Call WC Kit