



## Key Features

Fully compliant to BS 8300-2:2018



Standalone system for one zone



Light grey finish



Blue LED “halo” Braille-enhanced buttons



Designed and manufactured in the UK



## Overview

An emergency assistance alarm is a device or system designed to alert others or summon help in case of an emergency situation.

Building regulations require the installation of suitable emergency assistance alarm systems in areas such as disabled toilets. Crisis Assist Emergency Assistance Systems offer a comprehensive solution to provide support for individuals with disabilities or mobility challenges who need to request assistance.

Enabling quick response and assistance to individuals in need, Crisis Assist enhances safety and security by providing timely assistance and support during emergencies, helping to minimise risks and mitigate the impact of crisis situations. The Crisis Assist Disabled Toilet Alarm Kit includes everything needed to create a remotely monitored disabled toilet alarm and includes: a 1 Zone Controller, an Over Door Plate, a Ceiling Pull Plate, a Cancel Plate and a Disabled WC sticker.

Crisis EVC Disabled Toilet Kits provides a BS8300-2:2018 compliant accessible toilet solution including the “acknowledge” signalling required for remote locations. During an alert, the controller features audio and visual indication of an alarm. An integrated buzzer sounds and the unique blue “halo” indicator around the Accept button flashes for visual indication of a call. Once the staff member presses the Braille-enhanced Accept button, the sounder is muted and the LED halo turns solid until the alarm is cancelled or reset at the origin of the alarm.

## Tech Specs

### Controller

<b>Standards</b>	BS8300-2:2018 Building Regulations Approved Document M: 2010
<b>Supply</b>	230VAC +/- 10%
<b>Battery Backup</b>	Optional 600mA NIMH Rechargeable Battery
<b>Cabling</b>	Two core 0.4mm to 2.5mm CSA (max return resistance 10 Ohms)
<b>Relay Output</b>	0V 1A NO Volt Free
<b>Alarm Output</b>	50-80dBA
<b>Dimensions (W x H)</b>	146mm x 86mm
<b>Back Box Information</b>	35mm deep double gang flush or round corned metal surface box

### Over Door Plate, Cancel Plate & Ceiling Pull Plate

<b>Supply</b>	24VDC from Controller
<b>Cabling</b>	Two core 0.4mm to 2.5mm CSA (max return resistance 10 Ohms)
<b>Alarm Output</b>	Over Door Plate: 80dBA Cancel Plate: 75dBA Ceiling Pull Plate: n/a
<b>Dimensions (W x H)</b>	146mm x 86mm
<b>Back Box Information</b>	25mm deep single gang flush back box or round corned metal surface box. A matching brushed stainless surface pattress is available.

## Ordering Information

---

**Part Number****Description**

---

**36-418**

Crisis Assist Disabled Toilet Alarm Kit, 1 Line